

FLORIDA DEPARTMENT OF TRANSPORTATION
2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====		DIRECTION 2 =====		AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
0001		ON SR-200, 0.528 MI. E OF I-75 (UVL) HIT	E	21000	W	21000	42000 C	9.0	56.0F	14.1F
0003		ON SR-40, 0.297 MI. W OF CR-314A (RCLP) CAB NW	E	7300	W	7300	14600 C	9.5	56.0F	9.7A
0004		ON SR-40, 0.072 MI. W OF SE 183 AV RD (RVL)	E	4200E	W	4000E	8200 S	9.5	56.0F	11.0F
0006		ON US-441, 0.028 MI. N OF NW 145TH ST. (RC)	N	3800	S	3400	7200 C	9.5	56.0F	16.5A
0007		ON SR-200, 0.4 MI. S OF N. MAGNOLIA AVE. (RV)	N	6100	S	6400	12500 C	9.5	56.0F	20.0A
0008		ON SR-40, 0.788 MI E OF CR-225A (SW 80TH AV) (UC	E	12500	W	12000	24500 C	9.0	56.0F	6.6A
0011		ON US-441, 0.509 MI. N OF CR-42 (RCLP) CAB NW	N	13500	S	15000	28500 C	9.0	56.0F	6.9A
0012		ON US 27/301/441, 0.076 MI. S OF SE 38TH TER (RC	N	15000E	S	14500E	29500 S	9.0	56.0F	22.2P
0014		ON SR-441, 0.050 MI. N OF SE 119 PL (UC)	N	10500E	S	8600E	19100 S	9.0	52.9F	20.3P
0019		ON SR-464, 0.653 MI. E OF SR-200 CAB NW	E	16500E	W	15500E	32000 S	9.0	56.0F	15.1P
0020		ON SR-464, 0.218 MI. E OF SE 25TH AVE. HPMS BLT'	E	18000	W	18000	36000 C	9.0	56.0F	1.4A
0024		ON SR-40, 0.422 MI. NE OF SR-45 (US-41) (RC)	E	4600E	W	4300E	8900 S	9.5	56.0F	24.0P
0030		ON SR-40, 0.32 MI. E OF CR-328 (RV) CABINETS A &	E	9200	W	8900	18100 C	9.5	56.0F	14.7A
0032		ON SR-40, 0.26 MI. W OF CR-500A (UCLP)	E	16000E	W	15000E	31000 S	9.0	56.0F	21.9P
0033		ON US-27, 0.188MI. N OF 30TH AVE. (UCLP)	E	10000E	W	12000E	22000 S	9.0	56.0F	17.1P
0034		ON SR-40, 0.297 MI. E OF CR-500A (UVL)	E	11000E	W	11500E	22500 S	9.0	56.0F	15.1P

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
 2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
0038		CR-475, 0.45 MI S OF SR500 (HPMS)	N 2800E	S 3000E	5800 S	9.0	56.0F	9.8P
0040		ON US-27, 0.215 MI S OF CR-464A (UCLP)	N 14000E	S 16000E	30000 S	9.0	56.0F	20.5P
0042		ON SW BROADWAY STREET, 0.06 MILES E OF SW 7TH AV	E 1500	W 1600	3100 C	9.0	56.0F	13.6A
0043		ON US-301, 0.043 MI. N OF SE 118TH PL (RCLP)	N 6700	S 6900	13600 C	9.0	56.0F	10.9A
0049		CR-42, 528 FT W OF CR-25 IN WEIRSDALE AT RR SIGN	E 6200E	W 6000E	12200 S	9.0	56.0F	18.9P
0054		CR-42, 500 FT W OF CR-450 (HPMS)	E 2700E	W 2600E	5300 S	9.5	56.0F	8.0P
0055		CR-450, 500 FT S OF CR-42 (HPMS)	E 900E	W 950E	1850 S	9.5	56.0F	17.4P
0056		ON SR-40, 0.086 MI. SW OF SR-492 (UCLP)	E 11000E	W 13500E	24500 S	9.0	56.0F	14.4P
0062		ON SR-200, 0.260 MI. SW OF CR-464 (UVL)	N 19500	S 18000	37500 C	9.0	56.0F	14.1F
0083		ON SR-200, 0.9 MI. SW OF US-27/441 (UVL)	N 14000E	S 14000E	28000 S	9.0	56.0F	14.1F
0111		CR-42, 0.25 MI E OF CR-25 (HPMS)	E 5700E	W 5600E	11300 S	9.5	56.0F	18.0P
0118	T	SR-25/US-301,0.3 MI N OF SR-326,MARION CO.	N 17161	S 16982	34143 C	9.5	52.0A	17.6A
0122		ON SR-200, 0.516 MI. SW OF CR-475A (UCLP) BLT'25	N 20500	S 38000	58500 C	9.0	56.0F	30.3A
0123		SR 200, N OF SW 95TH ST. RD BLT'20	N 18500E	S 19500E	38000 S	9.0	56.0F	12.6P
0126		ON SR-200, 0.274 MI. NE OF CR-484 (RVL)	N 10500	S 11500	22000 C	9.0	56.0F	7.7A
0132		ON US-441, 0.12 MI. S OF SR-40 (UVL) BLT'24	N 19000E	S 22500E	41500 F	9.0	56.0F	13.4P

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
 V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
0136		ON US-441, 0.666 MI. N OF CR-484 (RVL)	N 16000E	S 15500E	31500 S	9.0	56.0F	7.8F
0166		ON US-441, 0.15 MI. S OF CR-320 (RVL)	N 4500E	S 4300E	8800 S	9.5	56.0F	13.2F
0173		ON CR-25, 0.8 MI. SE OF C-464 - (HPMS)	E 3300E	W 3200E	6500 S	9.0	56.0F	8.2P
0175		ON CR-25, 0.4 MI. S OF C-42 - (HPMS)	N 5200E	S 5400E	10600 S	9.0	56.0F	8.9P
0187		ON CR-25, 210 FT. N OF C-326 - (HPMS)	N 3500E	S 3400E	6900 S	9.0	56.0F	23.4P
0188		ON CR-25, 0.2 MI. NW OF SR-25 - HPMS '18	N 5300E	S 5500E	10800 S	9.0	56.0F	21.3P
0189		ON US-301, 0.404 MI. N OF CR-318 (RCLP) BUILT '2	N 7600E	S 7400E	15000 F	9.5	56.0F	16.2P
0200		ON US-41, 0.663 MI. N OF SR-40 (RV)	N 5900	S 6000	11900 C	9.0	56.0F	8.0A
0201		ON US-41, 1.1 MI. S OF CR-328 (UC)	N 2900E	S 3000E	5900 S	9.5	56.0F	13.4P
0214		CR-42, 0.1 MI E OF SR-35 (HPMS)	E 8100E	W 7800E	15900 S	9.0	56.0F	17.5P
0215		CR-42, 500 FT E OF CR-475 (HPMS)	E 2300E	W 2600E	4900 S	9.5	56.0F	17.4P
0222		ON SR-200, 0.2 MI. S OF CR-484 (RVLP)	N 9300E	S 9000E	18300 S	9.5	56.0F	10.7P
0233		ON US-441, 0.153 MI. S OF CR-318 (RVL)	N 5100E	S 4800E	9900 S	9.5	56.0F	16.4P
0237		ON US-441, 0.253 MI. SE OF CR-326 (RVL)	E 4700	W 4500	9200 C	9.5	56.0F	17.5A
0245		ON SR-40, 4.464 MI. E OF CR-314A (RCLP)	E 3300	W 3200	6500 C	9.5	56.0F	19.4A
0249	T	SR-464,140' EAST OF 47TH AVENUE,OCALA,MARION CO.	E 17327	W 17273	34600 C	9.0	52.5P	4.7A

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
 2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
0264	T	SR-40,566'E OF NE 24TH ST,OCALA,MARION CO.	E 11428	W 10535	21963 C	9.0	60.0A	6.4A
0317	T	I-75, 0.23 MI N OF WILLIAMS RD/SW 66TH ST O/P, M	0E	0E	140500 F	9.0	52.9F	25.3F
0380		ON US-41, 0.097 MI. N OF CITRUS CO. (RV)	N 10000E	S 11500E	21500 S	9.0	56.0F	30.2P
0384		ON US-27, 0.797 MI. W OF US-441 (RVL)	E 11000E	W 12000E	23000 S	9.0	56.0F	23.4P
0410		ON SR-19, 0.347 MI. S OF CR-314 (RC)	N 1200	S 1200	2400 C	9.5	56.0F	25.6A
0411		ON SR-19, 0.24 MI. N OF SR-40 (RV)	N 1100E	S 950E	2050 S	9.5	56.0F	15.5P
0423		ON US-441, 0.542 MI. SE OF US-301 (RC)	N 7600	S 7400	15000 C	9.0	56.0F	11.9A
0436		ON I-75, 0.527 MI. N OF CR-318 (RVL)	N 36000E	S 35500E	71500 F	10.5	52.9F	29.6P
0437		ON I-75, 1.469 MI. N OF SR-326 (RVL)	N 35000E	S 36000E	71000 S	10.5	52.9F	29.7P
0438		ON I-75, 0.986 MI. N OF US-27 (RCLP)	N 44000E	S 41500E	85500 F	9.0	52.9F	29.5P
0439		ON I-75, 0.376 MI. S OF US-27 (UVL)	N 36500	S 30000	66500 C	9.0	52.9F	27.9P
0440		ON I-75, 0.586 MI. S OF SR-40 (UVL)	N 51500E	S 49000E	100500 F	9.0	52.9F	25.3F
0442		ON US-301, 0.714 MI. S OF CR-200A S. LEG (RCLP)	N 7900E	S 9700E	17600 S	9.5	56.0F	25.0P
0443		ON US-301, 2.1 MI. N OF SR-326 (RVL) USE 360118	N 14500E	S 14500E	29000 F	9.5	56.0F	18.6P
0445	T	SR-200, 1.487 MI SW OF I-75	N 23090	S 23253	46343 C	9.0	57.6A	3.6A
0452		ON US-41, 0.11 MI. N OF WALMART SIGNAL (RCLP) HP	N 11500	S 10500	22000 C	9.0	56.0F	9.8A

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
 V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
 2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
0454		ON US-27, 0.314 MI. NW OF CR-25A (UVL) BLT'23	N 5100E	S 5600E	10700 S	9.0	56.0F	27.1P
0459		ON US-27, 0.574 MI. NW OF I-75 (RCLP)	E 9600E	W 11500E	21100 S	9.0	56.0F	25.2P
0462		ON SR-464, 0.111 MI. E OF SR-200 (UVL)	E 13000	W 13500	26500 C	9.0	56.0F	3.9F
0463		ON SR-464, 0.171 MI. W OF CR-464A (LP) CAB NW	E 15000E	W 16000E	31000 S	9.0	56.0F	16.6P
0464		ON SR-464, 0.56 MI. E OF CR-464A	E 14000	W 19000	33000 C	9.0	56.0F	5.7A
0465		ON SR-326, 0.245 MI. E OF I-75 (RVL)	E 14000E	W 12500E	26500 S	9.0	56.0F	11.0F
0466		ON US-441, 0.12 MI. S OF 1ST LEG TO CR-25A (RVL)	N 3800E	S 3900E	7700 S	9.5	56.0F	21.3P
0467		ON SR-25, 0.162 MI. E OF SR-35 (RVL)	N 6500E	S 6900E	13400 S	9.0	56.0F	7.8F
0468		ON SR-35, 0.104 MI. N OF SR-25 (RVL)	N 7100E	S 8100E	15200 S	9.0	56.0F	17.3P
0469		ON SR-35, 1.053 MI. S OF SR-464 (RCLP) NO CAB	N 11500	S 12000	23500 C	9.0	56.0F	8.1A
0470		ON SR-35, 0.41 MI. N OF SR-464	N 10000E	S 12000E	22000 S	9.0	56.0F	15.7P
0471		ON SR-35, 0.643 MI. S OF SR-40 (UV)	N 7400	S 8600	16000 C	9.0	56.0F	12.0A
0472		ON SR-40, 0.895 MI. E OF SR-35 (RV)	E 7800E	W 7600E	15400 S	9.0	56.0F	15.6P
0473		ON SR-200, 0.985 MI. NE OF CR-484 (RVL) BLT'20	N 12500E	S 14500E	27000 S	9.0	56.0F	27.3P
0474		ON SR-200, 2.498 MI. SW OF I-75 (RCLP) BLT'20	N 19500E	S 19500E	39000 S	9.0	56.0F	13.8P
0475		ON SR-40, 0.4 MI. W OF CR-225A (RCLP) CABINETS A	E 10000E	W 11000E	21000 S	9.5	56.0F	31.4P

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
 V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE	SITE TYPE	DESCRIPTION	DIRECTION 1	DIRECTION 2	AADT TWO-WAY	"K" FCTR	"D" FCTR	"T" FCTR
====	====	=====	=====	=====	=====	=====	=====	=====
0476		ON SR-40, 0.318 MI. W OF I-75 (RCLP)	E 14500E	W 15000E	29500 S	9.0	56.0F	15.6P
0477		ON SR-492, 0.22 MI. E OF US-27/441 (UVL) HPMS BL	E 7700E	W 9400E	17100 S	9.0	56.0F	16.3P
0479		ON SR-492, 1.107 MI. W OF SR-40 (UCLP) BLT'19	E 10500E	W 9600E	20100 S	9.0	56.0F	17.0P
0480		ON SR-492, 0.135 MI. E OF NE 36TH AVE. HPMS '18	E 4900	W 4100	9000 C	9.0	56.0F	6.9A
0482		ON US-301, 0.128 MI. S OF SR-326 (UVL)	N 11500E	S 9600E	21100 S	9.0	56.0F	11.5F
0483		ON US-441, 0.579 MI. S OF ALACHUA CO. (RCLP)	N 4200E	S 4000E	8200 S	9.5	56.0F	19.6P
0484		ON SR-40, 0.33 MI. W OF CR-315 (RCLP)	E 10000	W 9500	19500 C	9.5	56.0F	11.8A
0485		ON US-27, 0.571 MI. SE OF CR 225A (RVL)	E 9000E	W 9700E	18700 S	9.0	56.0F	32.3P
0486		ON SR-326, 0.356 MI. E OF US-301/441 (RCLP)	E 6100	W 5800	11900 C	9.0	56.0F	15.7A
0487		ON SR-326, 0.198 MI. E OF CR-200A (RVL) BLT'25	E 6600	W 6500	13100 C	9.0	56.0F	15.1A
0488		ON SR-326, 0.237 MI. N OF SR-40 (RCLP) HPMS '18	W 2100E	E 2100E	4200 S	9.0	56.0F	23.4P
0489		ON SR-492, 0.512 MI. W OF NE 17TH AV BLT'19 NW	E 7900E	W 9300E	17200 S	9.0	56.0F	23.3P
0490		ON SR-492, 0.417 MI. E OF NE 25TH AV BLT'19	E 8900E	W 8100E	17000 S	9.0	56.0F	19.1P
0491		ON SR-40, 0.551 MI. E OF US-27/441 (UCLP)	E 14500	W 14500	29000 C	9.0	56.0F	7.2A
1002		ON SR-326, 1.019 MI. W OF US-27/SR-200 (RCLP)	E 6800	W 5400	12200 C	9.0	56.0F	13.4A
1007		ON US-301, 0.188 MI. N OF CR-42 (RVL) HPMS '24	N 8300E	S 8100E	16400 S	9.0	56.0F	20.3P

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST; V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====		DIRECTION 2 =====		AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
1009		ON US-301, 0.169 MI. S OF CR-42 (RVL)	N	15500E	S	15000E	30500 S	9.0	56.0F	7.8F
1014		ON SR-40, 1.201 MI. E OF CR-315 (RVL) USE 360484	E	8100E	W	7700E	15800 F	9.5	56.0F	11.0F
1015		ON SR-19, 0.1 MI. N OF CR-316 (RCLP)	N	2100E	S	1900E	4000 S	9.5	56.0F	20.4P
1016		ON SR-19, 0.08 MI. S OF CR-316 (RVL)	N	2400E	S	2500E	4900 S	9.5	56.0F	13.5F
2000		I-75, RAMP FROM I-75 NB TO CR-484		0E		0E	6600 T	9.0	99.9W	10.0F
2001		I-75, RAMP FROM CR-484 TO I-75 NB		0E		0E	9500 T	9.0	99.9W	10.0F
2002		I-75, RAMP FROM I-75 SB TO CR-484		0E		0E	7600 T	9.0	99.9W	10.0F
2003		I-75, RAMP FROM CR-484 TO I-75 SB		0E		0E	5300 T	9.0	99.9W	10.0F
2004		I-75, RAMP FROM I-75 NB TO SR-200		0E		0E	8300 T	9.0	99.9W	14.1F
2005		I-75, RAMP FROM SR-200 TO I-75 NB		0E		0E	8600 T	9.0	99.9W	14.1F
2006		I-75, RAMP FROM I-75 SB TO SR-200		0E		0E	8400 T	9.0	99.9W	14.1F
2007		I-75, RAMP FROM SR-200 TO I-75 SB		0E		0E	8800 T	9.0	99.9W	14.1F
2008		I-75, RAMP FROM I-75 NB TO SR-40		0E		0E	7200 T	9.0	99.9W	3.9F
2009		I-75, RAMP FROM SR-40 TO I-75 NB		0E		0E	5300 T	9.0	99.9W	7.3F
2010		I-75, RAMP FROM I-75 SB TO SR-40		0E		0E	5300 T	9.0	99.9W	3.9F
2011		I-75, RAMP FROM SR-40 TO I-75 SB		0E		0E	7000 T	9.0	99.9W	3.9F

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
 2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
2012		I-75, RAMP FROM I-75 NB TO SR-500 (US-27)	0E	0E	8800 T	9.0	99.9W	13.2F
2013		I-75, RAMP FROM SR-500 (US-27) TO I-75 NB	0E	0E	2500 T	9.0	99.9W	13.2F
2014		I-75, RAMP FROM I-75 SB TO SR-500 (US-27)	0E	0E	2600 T	9.0	99.9W	13.2F
2015		I-75, RAMP FROM SR-500 (US-27) TO I-75 SB	0E	0E	9200 T	9.0	99.9W	13.2F
2016		I-75, RAMP FROM I-75 NB TO SR-326	0E	0E	14500 T	9.0	99.9W	11.0F
2017		I-75, RAMP FROM SR-326 TO I-75 NB	0E	0E	4000 T	9.0	99.9W	11.0F
2018		I-75, RAMP FROM I-75 SB TO SR-326	0E	0E	4900 T	9.0	99.9W	11.0F
2019		I-75, RAMP FROM SR-326 TO I-75 SB	0E	0E	3700 T	9.0	99.9W	11.0F
2020		I-75, RAMP FROM I-75 NB TO CR-318	0E	0E	2600 T	9.5	99.9W	10.0F
2021		I-75, RAMP FROM CR-318 TO I-75 NB	0E	0E	2600 T	9.5	99.9W	10.0F
2022		I-75, RAMP FROM I-75 SB TO CR-318	0E	0E	2400 T	9.5	99.9W	10.0F
2023		I-75, RAMP FROM CR-318 TO I-75 SB	0E	0E	2600 T	9.5	99.9W	10.0F
2024		I-75 SB, RAMP FROM SR-326 WB TO I-75 SB	0E	0E	9400 T	9.0	99.9W	11.0F
2026		I-75, NB OUT REST AREA (UC)	0E	0E	2700 T	9.5	99.9W	19.2F
2028		I-75, SB OUT REST AREA (UC)	0E	0E	2400 T	9.5	99.9W	19.2F
5005		ON SR-40, 1.29 MI. E OF US-27/301/441 (UVL)	E	W	14000E 14500E	28500 S	9.0	56.0F 27.6P

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
 V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
5010		ON SR-40, 0.07 MI. W OF US-27/411 (UVL) NW	E 12000	W 13000	25000 C	9.0	56.0F	3.9F
5014		ON SR-200, 0.37 MI. W OF US-27/441 (HPMS '16)BLT	E 14500E	W 13500E	28000 S	9.0	56.0F	15.6P
5017		ON US-441, 0.13 MI. N OF SR-464 (UVL)	N 12500	S 13000	25500 C	9.0	56.0F	11.3A
5018		ON US-441, 0.146 MI. S OF SR-200 (UCLP) NW	N 15500E	S 15500E	31000 S	9.0	56.0F	14.7P
5022		ON US-441, 0.17 MI. N OF SR-40 (UVL)	N 16000E	S 16500E	32500 S	9.0	56.0F	11.5F
5024		ON US-27, 0.104 MI. W OF SR-441/SR-492(UVL) BLT'	W 11000E	E 10500E	21500 S	9.0	56.0F	13.3P
5044		ON US-441, 0.176 MI. N OF SR-492 (UCLP)	N 16000	S 14500	30500 C	9.0	56.0F	10.5A
5046		ON SR-40, 1.376 MI. W OF SR-492 (UVL)	E 16000	W 16500	32500 C	9.0	56.0F	5.9A
5049		ON CR-200A, 0.15 MI. NE OF SR-25 (HPMS)	N 5100E	S 5300E	10400 S	9.0	56.0F	17.2P
5050		ON US-441, 0.061 MI. S OF CR-25A (UVL) HPMS '18	N 9100E	S 10500E	19600 S	9.0	56.0F	22.7P
5053		ON US-41, 0.549 MI. N. OF CR-484 (RCLP)	N 12000E	S 10500E	22500 S	9.0	56.0F	25.1P
5058		ON US-441, 0.152 MI. NW OF CR-484 (RVL)	N 13000	S 12500	25500 C	9.0	56.0F	9.0A
7001		NE 12TH AVE., SR-40 TO SR-492 (HPMS)	N 650E	S 450E	1100 S	9.0	56.0F	15.8P
7002		SW 20TH ST., 1 MI. W OF I-75 (HPMS SAMPLE)	E 6200E	W 6200E	12400 S	9.0	56.0F	13.3P
7003		NW 60TH AV., 0.2 MI. N OF SR-40 (HPMS)	N 6200E	S 6200E	12400 S	9.0	56.0F	13.5P
7004		ON CR-475A, 0.758 MI. W OF US-27/441 (HPMS)	E 2400E	W 2400E	4800 F	9.0	56.0F	11.9P

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====		DIRECTION 2 =====		AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
7005		SW 27TH AV., .085 MI N OF SR-200 (HPMS)	N	9100E	S	9900E	19000 F	9.0	56.0F	6.6P
7007		SUNSET HARBOR RD., 0.542 MI. E OF US-441 (HPMS)	E	2700E	W	2900E	5600 S	9.0	56.0F	7.6P
7008		NW 27TH AV., .075 MI. S OF NW 21 ST AV (HPMS)	N	3300E	S	3200E	6500 S	9.0	56.0F	23.2P
7009		FT. KING ST., .027 MI. E OF SE 9TH TERR. (HPMS)	E	2900E	W	2600E	5500 S	9.0	56.0F	9.6P
7010		FT. KING ST., .042 MI. W OF SE 15 TH AV. (HPMS)	E	2800E	W	2600E	5400 S	9.0	56.0F	4.0P
7011		FT. KING ST., .024 MI. E OF SE 19TH AVE. (HPMS)	E	5300E	W	3200E	8500 F	9.0	56.0F	1.7P
7012		SE 17TH ST., .08 MI. W OF SE 30 AVE. (HPMS)	E	1900E	W	1600E	3500 S	9.0	56.0F	14.9P
7013		MAGNOLIA AVE, 0.19 MI S OF NW 28TH ST (HPMS)	N	650E	S	400E	1050 S	9.0	56.0F	18.4P
7014		NE 25 TH AVE., 0.19 MI S OF SR-492 (HPMS)	N	7400E	S	7200E	14600 F	9.0	56.0F	3.2P
7015		NE 25TH AVE., 0.201 MI. S OF NE 24 TH ST. (HPMS)	N	4800E	S	4900E	9700 F	9.0	56.0F	16.6P
7016		NE 36TH AV., 0.2 MI S OF SR-492 (HPMS)	N	9400E	S	8700E	18100 F	9.0	56.0F	5.6P
7017		SE 36TH AVE., 0.568 MI. N OF SR-464 (HPMS)	N	8400E	S	9000E	17400 F	9.0	56.0F	4.0P
7018		SE 145 ST, 0.14 MI E OF CR-467 (HPMS)	E	850E	W	700E	1550 S	9.0	56.0F	23.5P
7019		SE 110 ST, 0.86 MI W OF SE 36 AVE (HPMS)	E	2000E	W	2100E	4100 S	9.5	56.0F	23.3P
7020		SE 92 PL RD, 0.18MI. E OF US-27/441 (HPMS)	E	5300	W	5800	11100 C	9.0	56.0F	9.7A
7021		NW 27TH AVE., 0.085 MI. S OF NW 21 ST ST. (HPMS)	N	2700	S	2700	5400 C	9.0	56.0F	17.5A

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
 2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
7022		OAK RD., 0.05 MI. S OF CR-464 (HPMS)	N 2700	S 2900	5600 C	9.0	56.0F	10.2A
7023		SW 13 ST., 0.1 MI. E OF SW 21 AV. (HPMS) SAMPLE	E 5700E	W 6000E	11700 S	9.0	56.0F	20.6P
7024		SW 19AV RD, 0.4 MI. E OF CR-475C (HPMS)	N 9700E	S 10000E	19700 F	9.0	56.0F	1.1P
7025		SW 60TH AVE, 0.075 MI N OF SW 80TH ST HPMS SAMPL	N 11000E	S 11000E	22000 S	9.0	56.0F	9.3P
7026		SE 3RD AVE, 0.1 MI S OF S MAGNOLIA (HPMS)	N 2200	S 2200	4400 C	9.0	56.0F	2.9A
7027		SE 3RD AVE, 0.095 MI N OF S MAGNOLIA (HPMS)	N 2200	S 1700	3900 C	9.0	56.0F	9.2A
7028		SE 11TH AVE, 0.04 MI E OF SE LAKE WEIR RD, OCALA	E 850E	W 850E	1700 S	9.0	56.0F	11.4P
7029		SE 11TH AVE, 0.05 MI N OF SR-464/SE 17TH ST (HPM	N 1300E	S 1300E	2600 S	9.0	56.0F	18.9P
7030		NE 52ND CT., 0.75 MI. S OF SHARPS FERRY RD. (HPM	N 650	S 500	1150 C	9.0	56.0F	8.9A
7031		SW 31ST AV./SW 33RD AV., 0.18 MI. N OF SW 13TH S	N 2500	S 2600	5100 C	9.0	56.0F	9.0A
7032		SW 38TH ST, 0.085 MI. W OF SW 60 AV. (HPMS)	E 5400E	W 5500E	10900 S	9.0	56.0F	8.1P
7033		SW-40 ST, 0.095 MI. E OF SW 46 AV. (HPMS)	E 5000	W 4900	9900 C	9.0	56.0F	6.8A
7034		ON CR-25, 0.95 MILES EAST OF CR-464 (HPMS)	E 3500E	W 3300E	6800 S	9.0	56.0F	16.5P
7035		CR-464, 0.04 MI. E OF SE 108 TERR RD (HPMS 22)	N 3100E	S 3000E	6100 S	9.0	56.0F	17.3P
7036		CR-200A, 0.15 MI. S OF CR-326 (HPMS)	N 3700	S 4000	7700 C	9.0	56.0F	9.8A
7038		CR-318, 0.1 MI W OF I-75 (HPMS)	E 1100E	W 1000E	2100 S	9.5	56.0F	31.7P

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
 V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
7039		CR-484, 0.18 MI E OF SR-200 (HPMS)	E 4200	W 3900	8100 C	9.0	56.0F	11.8A
7040		CR-484, 0.25 MI. E OF CR-475 (HPMS)	E 6300	W 5900	12200 C	9.0	56.0F	16.0A
7041		MARICAMP RD, 0.095 MI. N OF CR-25 (HPMS) SAMPLE	N 1300E	S 1600E	2900 S	9.0	56.0F	16.7P
7042		MARICAMP RD., 0.075 MI. W OF 108 TERR RD (HPMS)	N 5300	S 5300	10600 C	9.0	56.0F	12.4A
7043		MLK, 0.04 MI. S OF NW 5 ST. (HPMS)	N 6300E	S 6800E	13100 F	9.0	56.0F	5.4P
7044		NE 7TH ST., 0.5 MI. W OF NE 44 AV. (HPMS)	E 3700	W 4000	7700 C	9.0	56.0F	10.2A
7045		CR-467/36 AVE, 0.13 MI N OF CR-484/SE 135 ST (HP	N 2400	S 2500	4900 C	9.0	56.0F	10.2A
7046		CR-484 EXTENSION, 0.63 MILES WEST OF US-301 HPMS	E 7600E	W 7000E	14600 S	9.0	56.0F	21.0P
7047		SR200A - SR25, 1.82 MILES NORTH OF NE 35TH STREE	N 3700E	S 3900E	7600 S	9.0	56.0F	12.9P
7048		CR-42, 0.9 MILES WEST OF US-27/US-441/SR-500 (HP	E 8400	W 7800	16200 C	9.0	56.0F	9.9A
7049		ON CR-475, 0.59 MILES NORTH OF SE 52ND STREET, (N 5400E	S 5100E	10500 S	9.0	56.0F	14.6P
7051		SW34TH ST, 0.16 MI W OF SW 27TH AVE (HPMS)	E 4000	W 3200	7200 C	9.0	56.0F	7.7A
8000		CR-225A, 1150 FT N OF US-27 - HPMS	N 4400	S 4100	8500 C	9.0	56.0F	9.4A
8001		NW 110TH AVE, 700 FT N OF SR-40/BROADWAY AVENUE	N 2700E	S 2800E	5500 S	9.5	56.0F	10.0F
8002		W ANTHONY RD, 350 FT N OF US-441/N PINE AVENUE -	N 1000E	S 850E	1850 S	9.0	56.0F	25.0P
8003		NE 127TH STREET, 600 FT N OF CR-314 - OFF SYSTEM	N 400E	S 400E	800 T	9.5	56.0F	10.0F

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
 2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
8004		SE 182ND AVENUE ROAD, 400 FT N OF CR-42 - OFF SY	N 1400E	S 1600E	3000 T	9.5	56.0F	10.0F
8005		NE JACKSONVILLE RD, 100 FT N OF N MAGNOLIA AVE -	N 700E	S 600E	1300 S	9.0	56.0F	27.2P
8006		SW 32ND ST, 300 FT W OF SW 7TH ST - OFF SYSTEM	N 14000E	S 14000E	28000 S	9.0	56.0F	12.4P
8007		SE 38TH ST/36TH AVE, 450 FT E OF CR-464A - OFF S	E 3600E	W 3800E	7400 S	9.0	56.0F	11.1P
8008		SE 22ND AVENUE, 350 FT N OF SE 13TH ST - OFF SYS	N 850E	S 700E	1550 S	9.0	56.0F	16.9P
8009		NE 8TH AVE, 750 FT N OF SR-40/E SILVER SPRINGS B	N 4100E	S 3900E	8000 S	9.0	56.0F	15.6P
8010		NW 28TH ST, 450 FT E OF N PINE AVE - OFF SYSTEM	E 1200E	W 1800E	3000 S	9.0	56.0F	24.1P
8011		NE 24TH ST, 700 FT E OF CR-200A - OFF SYSTEM HPM	E 1800E	W 1600E	3400 S	9.0	56.0F	13.5P
8012		CR-314, 600 FT N OF SE 1ST RD - OFF SYSTEM	N 1200E	S 1200E	2400 F	9.5	56.0F	6.6P
8013		NE 19TH AVENUE, 200 FT N OF NE 14TH ST - OFF SYS	N 1500E	S 1100E	2600 F	9.0	56.0F	9.5P
8014		NE 35TH STREET, 650 FT E OF NE 36TH AVE - OFF SY	E 3600E	W 3700E	7300 S	9.0	56.0F	20.8P
8015		NE 3RD ST, 700 FT E OF N MAGNOLIA AVE - HPMS	E 600E	W 650E	1250 S	9.0	56.0F	16.2P
8016		CR-314/NE 7TH ST, 1200 FT E OF NE 71ST TER - OFF	E 1800E	W 1800E	3600 S	9.0	56.0F	11.1P
8017		SE 95TH ST, 200 FT E OF CR-464C - OFF SYSTEM	E 2600E	W 2600E	5200 S	9.5	56.0F	10.0F
8018		SE 108 TERRACE RD, 300 FT N OF CR-25/OCALA RD -	N 1100E	S 1200E	2300 F	9.0	56.0F	15.3P
8019		SE 100TH AVE, 250 FT N OF SE 147TH PL/SUNSET HAR	N 2100E	S 2200E	4300 S	9.0	56.0F	15.0P

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
 V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
8020		NE 35TH ST, 350 FT E OF NE 25TH AVE - OFF SYSTEM	E 4200E	W 4600E	8800 S	9.0	56.0F	24.3P
8021		NE 14TH STREET, E OF MAGNOLIA AVENUE - OFF SYSTE	E 1700E	W 1200E	2900 S	9.0	56.0F	29.1P
8022		NE 1ST ST ONEWAY NB, 50 FT N OF SR-40 - OFF SYST	0E	0E	1900 F	9.0	99.9W	15.4P
8023		NE 35TH STREET, 300 FT E OF NW 16TH AVE - OFF SY	E 8100E	W 8700E	16800 S	9.0	56.0F	23.7P
8024		NW 193RD ST, 700 FT E OF NW 100TH AVE - OFF SYST	E 200E	W 200E	400 F	9.5	56.0F	12.8P
8025		NE 175TH ST, 800 FT E OF US-301 - OFF SYSTEM	E 1200E	W 1300E	2500 S	9.5	56.0F	10.0F
8026		NW 112 PLACE, 350 FT N OF CR-326 - OFF SYSTEM	N 200E	S 150E	350 F	9.5	56.0F	14.1P
8027		NW 100TH ST, 600 FT E OF NW HIGHWAY 225A - OFF S	E 350E	W 300E	650 F	9.5	56.0F	11.8P
8028		SW 140TH AVE, 700 FT S OF HWY 328 - OFF SYSTEM	S 1100E	N 1400E	2500 F	9.5	56.0F	10.9P
8029		NW 44TH AVE, 1150 FT N OF US-27/BONNIE HEATH BLV	N 4800E	S 5100E	9900 S	9.0	56.0F	18.8P
8030		NE 25TH AVENUE, 350 FT N OF NE 35TH ST - OFF SYS	N 3100E	S 3300E	6400 S	9.0	56.0F	15.2P
8031		SE 52ND ST, 500 FT E OF US-441 - OFF SYSTEM	E 2500E	W 2800E	5300 S	9.0	56.0F	21.3P
8032		SW 66TH ST, 400 FT E OF SR-200 - OFF SYSTEM	E 4200E	W 4200E	8400 S	9.0	56.0F	6.3P
8034		NE 55TH AVE, 350 FT N OF NE 35TH ST - HPMS '15	N 2900E	S 2900E	5800 F	9.0	56.0F	17.0P
8035		NE 55TH AVE, 450 FT N OF SR-326 - OFF SYSTEM	N 1500E	S 1500E	3000 F	9.5	56.0F	19.1P
8036		MAGNOLIA ONEWAY SB, 150 FT N OF SR-40 - OFF SYST	0E	0E	3600 F	9.0	99.9W	10.3P

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE ====	SITE TYPE ====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
8038		SW 80TH AVE, 1350 FT N OF SR-200 - OFF SYSTEM HP	N 6700E	S 6300E	13000 S	9.0	56.0F	10.4P
8039		NW 35TH ST, 500 FT E OF NW 27TH AVE - OFF SYSTEM	E 5700E	W 5100E	10800 S	9.0	56.0F	26.6P
8040		SW 80TH ST, 300 FT E OF SW 19TH AVE RD - OFF SYS	E 2600E	W 2600E	5200 S	9.0	56.0F	11.7P
8041		SE 80TH ST, 350 FT E OF US-441 - OFF SYSTEM	E 3000E	W 2800E	5800 S	9.0	56.0F	11.0P
8042		SE 41ST COURT, 500 FT N OF JUNIPER CIRCLE - OFF	N 2800E	S 2600E	5400 S	9.0	56.0F	4.9P
8043		SW 19TH AVENUE RD, 50 FT N OF CR-328 - OFF SYSTE	N 2800E	S 2500E	5300 S	9.0	56.0F	11.8P
8044		NW 135TH ST, 400 FT E OF CR-225 - OFF SYSTEM	E 70E	W 60E	130 F	9.5	56.0F	13.0P
8045		SE 18TH AVE, 400 FT N OF SE 31ST STREET - OFF SY	N 4200E	S 3800E	8000 S	9.0	56.0F	19.0P
8046		SE 24TH STREET/SE 28TH STREET, E OF MARICAMP ROA	E 4600E	W 4500E	9100 S	9.0	56.0F	4.0P
8047		SE 31ST ST, 400 FT E OF SE 5TH TERRACE - OFF SYS	E 9400E	W 9200E	18600 S	9.0	56.0F	11.8P
8048		SW 1ST AVE, 350 FT N OF SR-464/SW 17TH ST - OFF	N 2600E	S 2400E	5000 S	9.0	56.0F	5.7P
8049		SW 103RD ST RD, 250 FT E OF SR-200 - OFF SYSTEM	E 2900E	W 2900E	5800 S	9.0	56.0F	5.6P
8050		SW 140TH AVE, 400 FT N OF CR-484 - OFF SYSTEM	N 1400E	S 1200E	2600 R	9.0	56.0F	10.0F
8051		NW 38TH AVE, 700 FT N OF SR-40 - OFF SYSTEM	N 950E	S 900E	1850 F	9.0	56.0F	20.6P
8053		NW 3RD ST, 350 FT E OF US-27/PINE ST - OFF SYSTE	E 650E	W 950E	1600 F	9.0	56.0F	15.1P
8054		POWELL RD, 250 FT E OF CR-40W/CEDAR ST - OFF SYS	E 2100E	W 1800E	3900 S	9.0	56.0F	10.0F

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
8055		SW 38TH AVE, 350 FT N OF SW 38TH CT - OFF SYSTEM	N 3300E	S 3700E	7000 S	9.0	56.0F	4.3P
8056		CR-314, 950 FT N OF SR-40 - OFF SYSTEM	E 1900E	W 1800E	3700 S	9.5	56.0F	10.0F
8058		CR-318, 450 FT E OF NW 53RD CT - OFF SYSTEM	E 2000E	W 2000E	4000 S	9.5	56.0F	34.1P
8059		CR-484, 600 FT E OF ADAMS ST - OFF SYSTEM	E 5000E	W 5200E	10200 S	9.0	56.0F	20.6P
8060		CR-42, 550 FT E OF CR-450 (SE HWY 450) - OFF SYS	E 2000E	W 950E	2950 S	9.5	56.0F	13.5P
8061		CR-326, 500 FT E OF LEVY CO/L - OFF SYSTEM	E 1000E	W 1000E	2000 F	9.5	56.0F	13.3P
8062		CR-315, 750 FT N OF SR-40 - OFF SYSTEM	N 2400E	S 2500E	4900 S	9.5	56.0F	10.0F
8063		CR-464C, 650 FT N OF CR-25 - OFF SYSTEM HPMS '17	N 2300E	S 2300E	4600 S	9.0	56.0F	23.7P
8064		CR-320, 100 FT E OF LEVY CO/L - OFF SYSTEM	E 250E	W 250E	500 F	9.5	56.0F	15.6P
8065		SW 60TH AVE, 450 FT N OF SW 20TH ST - OFF SYSTEM	N 9100E	S 8900E	18000 S	9.0	56.0F	13.9P
8066		SW 60TH AVE, 700 FT N OF SR-200 - OFF SYSTEM	N 8600E	S 9100E	17700 S	9.0	56.0F	12.7P
8067		SW 107 PL, 650 FT E OF SW 16TH AVE/CR-475A - OFF	E 2500E	W 2900E	5400 S	9.5	56.0F	9.6P
8068		SE 80TH AVE, 500 FT E OF CR-475/MAGNOLIA - OFF S	E 3100E	W 3400E	6500 S	9.0	56.0F	27.6P
8069		W ANTHONY RD, 450 FT N OF NE 35TH ST - OFF SYSTE	N 2900E	S 2900E	5800 S	9.0	56.0F	13.3P
8070		CR-40, 700 FT E OF CR-336 - OFF SYSTEM	E 950E	W 1000E	1950 F	9.5	56.0F	8.7P
8071		CR-316, 500 FT E OF NE JACKSONVILLE RD/CR-200A -	E 1100E	W 1100E	2200 S	9.5	56.0F	26.9P

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
8072		SE 25TH AVE, 750 FT N OF SE MARICAMP RD - OFF SY	N 9000E	S 8800E	17800 S	9.0	56.0F	12.4P
8073		SW M L KING BLVD, 200 FT NE OF SR-464/SW 17TH ST	N 3100E	S 3200E	6300 S	9.0	56.0F	8.7P
8074		CR-329, 400 FT N OF I-75 - OFF SYSTEM	N 800E	S 850E	1650 F	9.5	56.0F	17.7P
8075		CR-329, 750 FT E OF CR-25A/NW GAINES RD - OFF SY	E 1300E	W 1200E	2500 F	9.5	56.0F	15.2P
8076		CR-314A, 550 FT N OF SE 137TH AVE - OFF SYSTEM	N 1900E	S 1900E	3800 F	9.5	56.0F	16.9P
8077		CR-225, 750 FT N OF US-27/BONNIE HEATH BLVD - OF	N 650E	S 650E	1300 S	9.5	56.0F	10.0F
8078		CR-316, 600 FT E OF CR-329 - OFF SYSTEM	E 400E	W 400E	800 F	9.5	56.0F	15.7P
8079		CR-316, 250 FT E OF NW 41ST TER - OFF SYSTEM	E 650E	W 650E	1300 F	9.5	56.0F	10.4P
8080		CR-452, 0.7 MI N OF LAKE CO/L - OFF SYSTEM	N 3100E	S 3300E	6400 S	9.5	56.0F	13.4P
8081		SE 17TH/MARICAMP RD, 200 FT S OF CLEAR RD - OFF	N 7900E	S 7800E	15700 S	9.0	56.0F	16.0P
8082		LAKE WEIR RD, 550 FT N OF SE 38TH ST - OFF SYSTE	N 3200E	S 2700E	5900 S	9.0	56.0F	8.1P
8083		NW 16TH AVE, 800 FT N OF NW 22ND ST - OFF SYSTEM	N 3800E	S 3600E	7400 S	9.0	56.0F	21.2P
8084		CR-464, 0.3 MI W OF NW 157TH CT - OFF SYSTEM	E 950E	W 1000E	1950 F	9.5	56.0F	15.0P
8085		CR-225A, 250 FT N OF CR-326 - OFF SYSTEM	N 1600E	S 1700E	3300 F	9.5	56.0F	21.5P
8086		NE 90TH STREET RD, 0.3 MI E OF NE 92ND AVE - OFF	E 350E	W 300E	650 F	9.5	56.0F	16.2P
8087		SW 27TH AVENUE, 0.25 MI N OF CR-484 - OFF SYSTEM	N 3200E	S 4000E	7200 F	9.0	56.0F	9.4P

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
8088		SW 7TH AVENUE, 0.5 MI N OF SW 32ND STREET - OFF	N 2700E	S 1900E	4600 S	9.0	56.0F	17.6P
8089		NE 97TH ST, 250 FT E OF NE JACKSONVILLE RD - OFF	E 200	W 350	550 C	9.0	56.0F	6.6A
8090		CR-315, 350 FT N OF CR-21/CR-315 - OFF SYSTEM	N 1700E	S 2200E	3900 S	9.5	56.0F	10.0F
8091		SW 87TH PL, 950 FT E OF SW 27TH AVE - OFF SYSTEM	E 1500E	W 1700E	3200 F	9.5	56.0F	5.6P
8093		SE 36TH AVE, 300 FT S OF SE 8TH ST - OFF SYSTEM	N 9100E	S 8100E	17200 S	9.0	56.0F	26.6P
8094		SE FT KING ST, 350 FT E OF NE 41ST AVE - OFF SYS	E 4000E	W 4100E	8100 S	9.0	56.0F	5.8P
8096		NE 25TH AVE, 500 FT N OF NE 28TH ST - OFF SYSTEM	N 3900E	S 3700E	7600 S	9.0	56.0F	15.7P
8097		NE 36TH AVE, 150 FT N OF NE 24TH ST - OFF SYSTEM	N 6300E	S 5700E	12000 S	9.0	56.0F	30.6P
8098		NE 36TH AVE, 0.5 MI S OF SR-326 - OFF SYSTEM	N 1900E	S 1600E	3500 S	9.0	56.0F	27.9P
8099		SE 95TH ST, 1 MI E OF SE 7TH AVE - OFF SYSTEM	E 1000E	W 1100E	2100 S	9.5	56.0F	21.0P
8100		SE 95TH ST, 0.25 MI E OF CR-475/MAGNOLIA AVE - O	E 950E	W 1000E	1950 S	9.5	56.0F	8.6P
8101		NW 95TH ST, 0.5 MI E OF US-441 - OFF SYSTEM	E 950E	W 750E	1700 F	9.5	56.0F	4.4P
8102		NE 36TH AVE, 0.2 MI S OF CR-329 - OFF SYSTEM	N 700E	S 600E	1300 S	9.5	56.0F	38.9P
8103		SW 180TH AVE, 0.5 MI S OF SR-40W/BROADWAY AVE -	N 950E	S 950E	1900 S	9.5	56.0F	28.1P
8104		NE 47TH AVE, 0.5 MI S OF CR-316 - OFF SYSTEM	N 450E	S 400E	850 F	9.5	56.0F	7.1P
8105		NE 165TH ST/MILLWOOD RD, 0.5 MI E OF US-441 - OF	E 350E	W 350E	700 F	9.5	56.0F	13.3P

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
 2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE =====	SITE TYPE =====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
8106		SE 95TH ST RD, 500 FT E OF SE 180TH AVE RD - OFF	E 1500E	W 1500E	3000 F	9.5	56.0F	6.7P
8107		NW 193RD ST, 500 FT E OF CR-329 - OFF SYSTEM	E 150E	W 150E	300 F	9.5	56.0F	10.1P
8108		SW 49TH AVE, 0.2 MI N OF SW103RD ST - OFF SYSTEM	N 8400E	S 8000E	16400 S	9.0	56.0F	4.4P
8109		SE FT KING ST, 650 FT E OF SE 25TH AVE - OFF SYS	E 4200E	W 4300E	8500 S	9.0	56.0F	14.8P
8110		SW 32ND ST, 600 FT E OF CR-475/SE 3RD AVE - OFF	E 11500E	W 12000E	23500 S	9.0	56.0F	8.4P
8111		BASELINE RD EXT, 0.24 MI N OF US-441 - OFF SYSTE	N 2400E	S 2500E	4900 S	9.0	56.0F	10.0F
8112		CR-328, 500 FT W OF SW 140TH AVE/WOODRIDGE DR -	E 1800E	W 1900E	3700 F	9.5	56.0F	16.7P
8113		SE 110TH ST, 900 FT E OF OAK RD, BELLEVIEW - OFF	E 1700E	W 1700E	3400 S	9.0	56.0F	5.6P
8114		CR-329, 650 FT W OF NE 36TH AVE - OFF SYSTEM	E 1100E	W 1100E	2200 F	9.5	56.0F	9.6P
8115		CR-318, 1 MI E OF I-75 - OFF SYSTEM - HPMS	E 2800E	W 3000E	5800 S	9.5	56.0F	10.0F
8116		CR-316, 1 MI E OF US-27/BONNIE HEATH BLVD - OFF	E 750E	W 700E	1450 F	9.5	56.0F	22.4P
8117		MARTIN LUTHER KING JR AVE, 200 FT S OF SW 5TH ST	N 6500E	S 7300E	13800 F	9.0	56.0F	6.2P
8118		CR-467/SE 36TH AVE, 500 FT N OF CR-42 - OFF SYST	N 1700E	S 1600E	3300 F	9.5	56.0F	6.1P
8119		CR-467/SE 36TH AVE, 500 FT N OF SE 110TH ST - OF	N 3100E	S 2900E	6000 T	9.0	56.0F	10.0F
8120		SE 44TH AVE RD, 60' N OF 45TH CT - OFF SYSTEM	N 3900E	S 3900E	7800 R	9.0	56.0F	10.0F
8121		SE 64TH AVE RD, 430' N OF SR 464 - OFF SYSTEM	N 3700E	S 3800E	7500 R	9.0	56.0F	10.0F

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
 V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE ====	SITE TYPE ====	DESCRIPTION =====	DIRECTION 1 =====	DIRECTION 2 =====	AADT TWO-WAY =====	"K" FCTR =====	"D" FCTR =====	"T" FCTR =====
8122		PINE RD, 100' N OF PINE RADIAL LN - OFF SYSTEM	E 2000E	W 1900E	3900 R	9.0	56.0F	10.0F
8124		BAHIA RD, 600' N OF MIDWAY RD - OFF SYSTEM	N 1800E	S 1600E	3400 R	9.0	56.0F	10.0F
8125		OAK RD, 500' N OF PALM RUN - OFF SYSTEM	E 1100E	W 1100E	2200 R	9.0	56.0F	10.0F
8126		SILVER RD, 40' N OF PINE RD T INTERSECTION - OFF	N 1100E	S 1000E	2100 F	9.0	56.0F	1.7P
8127		EMERALD RD 50' E OF SPRING DR - OFF SYSTEM	E 1000E	W 1000E	2000 R	9.0	56.0F	10.0F
8128		SPRING RD, 50' N OF SPRING LANE - OFF SYSTEM	N 1000E	S 1000E	2000 R	9.0	56.0F	10.0F
8129		JUMIPER RD, 100' S OF ASPEN RD - OFF SYSTEM	E 1900E	W 1900E	3800 R	9.0	56.0F	10.0F
8130		SE79TH ST, 250' W OF SE 41ST CT - OFF SYSTEM	E 3600E	W 3600E	7200 R	9.0	56.0F	10.0F
8131		CHESTNUT RD, 250' W OF SR 35 - OFF SYSTEM	E 1700E	W 1800E	3500 R	9.0	56.0F	10.0F
8132		SE 102ND PLACE, 1000' W OF US 27 - OFF HPMS '19	E 2200E	W 2100E	4300 F	9.0	56.0F	2.6P
8133		SE 55TH AVE RD, 600' S OF US 27 - OFF SYSTEM	N 1100E	S 1400E	2500 R	9.0	56.0F	10.0F
8134		SE 114TH ST RD, 0.4 MI W OF SR 464 - OFF SYSTEM	E 2300E	W 2300E	4600 R	9.0	56.0F	10.0F
8135		SW 80TH AVE, 250' S OF SW 100TH ST - OFF SYSTEM	N 2100E	S 2200E	4300 R	9.0	56.0F	10.0F
8136		MARION OAKS TRAIL, 500' E OF 73RD AVE RD - OFF S	E 1300E	W 1300E	2600 F	9.0	56.0F	4.0P
8137		MARION OAKS MANOR, 400' W OF MARION OAKE DR - OF	E 1100E	W 1100E	2200 R	9.0	56.0F	10.0F
8138		MARION OAKS BLVD. 500' S OF SW COUNTY HWY 484 -	N 8400E	S 8100E	16500 R	9.0	56.0F	10.0F

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST;
V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF

FLORIDA DEPARTMENT OF TRANSPORTATION
 2025 ANNUAL AVERAGE DAILY TRAFFIC REPORT - REPORT TYPE: ALL

COUNTY: 36 MARION

SITE	SITE TYPE	DESCRIPTION	DIRECTION 1	DIRECTION 2	AADT TWO-WAY	"K" FCTR	"D" FCTR	"T" FCTR
====	====	=====	=====	=====	=====	=====	=====	=====
8139		MARION OAKS COURSE 400' S OF SW COUNTY HWY 484 -	N 3900E	S 4200E	8100 R	9.0	56.0F	10.0F
8140		MARION OAKS LANE, 200' W OF SW 43RD COURT RD	E 1100E	W 1000E	2100 R	9.0	56.0F	10.0F
8141		MANOR OAKS DR, 500' W OF MARION OAKS BLVD HPMS '	E 2500E	W 2400E	4900 F	9.0	56.0F	2.1P
8142		SE FOSS RD, 65' W OF RR,N OF SE STETSON RD	E 2100E	W 2500E	4600 R	9.0	56.0F	10.0F
8143		NE 160TH AVE RD, N OF CR 316 - OFF SYSTEM	N 400E	S 400E	800 R	9.5	56.0F	10.0F
8144		SE 110 ST RD AT SR 25.- OFF SYSTEM	N 1600E	S 1700E	3300 R	9.0	56.0F	10.0F
8145		SW 43RD CT. N. OF SW 40TH - OFF SYSTEM	N 1700E	S 1800E	3500 F	9.0	56.0F	8.7P
8146		SW 49 AVE- OFF SYSTEM	N 7300E	S 7500E	14800 F	9.0	56.0F	10.0F
8147		NW 35 AVE S OF NW 35TH ST -OFF SYSTEM	N 4200	S 4300	8500 C	9.0	56.0F	2.3A
8148		SW 44 AVE - OFF SYSTEM	N 600E	S 650E	1250 F	9.0	56.0F	10.0F
8149		SW 49 CT RD S OF MARION OAKS TRL - OFF SYSTEM	N 4900	S 5000	9900 C	9.0	56.0F	5.0A
8150		SW 44TH AVE/NW 44TH AVE S OF SR 40 - OFF SYSTEM	N 4500E	S 4800E	9300 F	9.0	56.0F	10.0F
8151		SW 17TH PL SERVICE RD - OFF SYSTEM	E 350	W 350	700 C	9.5	56.0F	3.8A
8152		SW 16TH LN SERVICE ROAD - OFF SYSTEM	E 250	W 550	800 C	9.5	56.0F	4.5A
8153		SW 17TH LOOP SERVICE ROAD - OFF SYSTEM	E 100	W 250	350 C	9.5	56.0F	8.0A

SITE TYPE : BLANK= PORTABLE; T= TELEMETERED

"K" FACTOR : DEPARTMENT ADOPTED STANDARD K FACTOR BEGINING WITH COUNT YEAR 2011

AADT FLAGS : C= COMPUTED; E= MANUAL EST; F= FIRST YEAR EST; S= SECOND YEAR EST; T= THIRD YEAR EST; R= FOURTH YEAR EST; V= FIFTH YEAR EST; 6= SIXTH YEAR EST; X= UNKNOWN

"D/T" FLAGS : A= ACTUAL; F= FACTOR CATG; D= DIST FUNCL; P= PRIOR YEAR; S= STATEWIDE DEFAULT; W= ONE-WAY ROAD; X= CROSS REF